

CONCRETE

GROUT PRODUCTS

Morse Industries is now offering Non-Shrink Cement for all your wet glazing and anchoring needs. Rockite and Kwixset are recognized as the industry leaders in anchoring cement products. Both Rockite for interior projects and Kwixset for exterior projects are fast setting and develop compression strength that is more than twice that of conventional concrete.



KWIXSET

EXTERIOR ANCHORING



Part #: G42-10402

Product Features:

- Portland cement based
- Non-shrink product
- Non-metallic grout for use in interior or exterior glazing applications
- Recommended Mix:
50lbs Kwixset to 1.5 gal water
- Yield: .45 cu ft./50lb pail
- Setting Time: 5-20 Minutes
- Takes stress loading in 2 hours and fully sets over 7 days
- Compressive Strength:
4100psi after 1 hour
8100psi after 3 days
10,500psi after 28 days

ROCKITE

FOR ANCHORING AND PATCHING



Part #: G42-10051

Product Features:

- Gypsum based
- Non – Shrink
- Non- Metallic grout for use in interior glazing applications
- Dry locations only
- Recommended Mix:
50lbs Rockite to 1.75 gal water
- Yield: .45cu ft/50lb pail
- Setting Time: <30 Minutes
- Takes stress loading in 2 hours and fully sets over 7 days
- Compressive Strength:
4500psi after 1 hour
5000psi after 1 day
8000psi after 7 days

* Important – Kwixset must not come in contact with unprotected aluminum or laminated glass

CALL US
800.325.7513